Product Data Sheet

🖀 1-888-452-HANA (4262) 📮 info@hanawireless.com

▲ 1-688-452-HANA (4202) ▲ Into@nahawireless.com
☑ 9465 Southampton Pl, Boca Raton, FL 33434, USA



Model: HW2-N12-V

12x10x5 Inch Weatherproof Enclosure with Slotted Mounting Plate, Vent System



Features

- Molded Fiberglass Reinforced Polyester (FRP)
- Stainless steel quick-release latches with padlock hasps
- NEMA Type 3R, 3RX / IP24 rated, fully gasketed lid
- Integral mounting flange, mast mounting option
- Aluminum mounting plate, ventilation system, patented (US8014157) slotted accessory mounting design

Applications

- Remote wireless LAN Wi-Fi equipment installations
- Indoor and outdoor installations
- Rapid deployment and hotspot installations
- Harsh and corrosive environments
- Protection of equipment from theft and damage

Specifications

MaterialFRPColorTool Gray – RAL 7035Voltage VacN/AHeater F° (C°)N/AHeat Temperature ON/OFF F° (C°)N/AFan Power WattN/A	
Voltage VacN/AHeater F° (C°)N/AHeat Temperature ON/OFF F° (C°)N/A	
Heater F° (C°)N/AHeat Temperature ON/OFF F° (C°)N/A	
Heat Temperature ON/OFF F° (C°) N/A	
Fan Power Watt N/A	
Fan Temperature ON/OFF F° (C°) N/A	
Mounting Plate Dimensions in (mm) 10.8 (274) x 8.9 (226) x 0.1 (2	2.5)
Mounting Plate Material Anodized Aluminum	
Weight lb (kg) 7.8 (3.5)	
Outside Dimensions, Max in (mm) 13.3 (338) x 11.3 (287) x 5.6	(142)
Inside Dimensions in (mm) 12.0 (305) x 10.0 (254) x 4.8	(123)
Flame Rating UL 94-5V	
RoHS Compliant	
Environmental Rating NEMA - IP 3R, 3RX - 24	
Cable Feed 1/2in Conduit Connector	

Package Specifications

Package Quantity	1 per Carton
Length in (mm)	16.0 (406)
Width in (mm)	16.0 (406)
Depth in (mm)	16.0 (406)
Weight lb (kg)	8.3 (3.8)

Wireless That Works



