



Features

- Dual 3" Vents with Rain Shields to Expel Heat
- Includes 2.0mm Thick Finished Aluminum Equipment Mounting Plate
- Meets NEMA Type 3R, 3RX and IP24
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Grommets, Zip Ties, Cable Management Loops and Ground Wire
- Knock-Out Holes on Top & Bottom
- Optional Pole Mount Kits Available

Description

The **Altelix NP171406VP** Vented PC+ABS Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring and small devices in harsh environments.

Construction and Features

This configuration includes a 2.0mm thick aluminum plate for mounting and securing equipment. The enclosure is IP24 rated and features a fully gasketed door to protect from dust and water ingress. The door features reinforced hinges, dual latches and a tamper-proof locking screw with key to secure the enclosure. There is also a provision for padlock use. Knock-outs are provided on the enclosure for additional wiring.

Ventilation

This enclosure features two 3 inch air vents. Rain shields help prevent rain water from entering the enclosure.

Complete with Cable Grommets and Wire Management Accessories

This enclosure includes an assortment of cable grommets that can be installed in the knock-out holes for a weather resistant seal. The included accessory kit contains wall anchors, zip ties, wire management loops, and ground wire, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Color	Gray (See Altelix.com for full list of available colors)
Outer Dimensions (Height x Width x Depth)	16.5 x 13.7 x 6.5 Inches (420 x 348 x 166 mm)
Inner Dimensions* (Height x Width x Depth)	14.0 x 9.0 x 4.0 Inches (356 x 229 x 102 mm)
Mounting Plate Material	0.08 In. (2.0mm) Aluminum
Mounting Plate Dimensions	11.2 x 14.8 In. (285 x 378 mm)
Weight	5.7 lbs. (2.5 kg)
Ratings	NEMA Type 3R, 3RX / IP24
Flame Rating	Meets UL94-V0
Knockout Sizes (Diameter)	(4) 0.62 in. (16 mm) (4) 1.02 in. (26 mm) (4) 1.30 in. (33 mm)

*Interior dimensions represent maximum space available for equipment.